MPN: 0070-06001

Gemini 2MP Pinhole-kamera med 2,8 mm lins, PoE, inomhus - NDAA

Gemini SX 722



Geminis unika delade formfaktor kan enkelt integreras i bankomater, varuautomater eller serviceterminaler där det finns mycket begränsat installationsutrymme för eftermarknadskameror. Kameran är också lämplig för kassadiskar, hotellreceptioner och alla platser där en diskret installation krävs.

- 1/2,8" Sony Progressiv CMOS
- 1920 × 1080 @ 30fps HDR (2MP)
- Unik delad design
- H.265/H.264/MJPEG samtidigt
- Låg latens streaming
- Stöd för fyra strömmar
- 3D rörelsekompenserad brusreducering
- Textöverlägg och sekretessfilter
- Stöd för Micro SD/SDHC/SDXC-kort
- 5 års garanti

Specifikationer

Camera	**Camera pan control**	No
	Lens viewing angle, horizontal	112 °
	Lens viewing angle, vertical	61.9 °
	Minimum illumination	0,22 lx
Design	**Housing material**	Metal
	Product colour	Black
	Weatherproof	No
Image sensor	**Number of effective pixels (H x V)**	1920x1080 pixlar
	Optical sensor size	1/2.8 "
	Progressive scan	Yes
	Sensor type	CMOS
Legal Information	**ADR Information**	No restrictions
	Country of Origin	Taiwan
	Tariff No.	8525890000
	UNSPSC Code	46171610
Lens system	**Fixed focal length**	2,8 mm
Network	**Ethernet LAN**	Yes
	Wi-Fi	No
Operational conditions	**Operating relative humidity (H-H)**	10 - 90 %
	Operating temperature (T-T)	-30 - 55 ° C

Other features	**Dimensions (WxDxH)**	26x26x43 mm
Package dimensions	**Gross Weight (Package, kg)**	0,5 kg
Performance	**Connectivity technology**	Wired
	NDAA Compliance	Yes
	Placement supported	Indoor
	Type	IP security camera
	Wide Dynamic Range (WDR)	Yes
Power	**Power consumption (max)**	4,56 W
	Power consumption (Power over Ethernet (PoE))	5,28 W
	Power over Ethernet (PoE)	Yes
	Power source type	PoE, DC
Product dimensions	**Net Weight (Product, kg)**	0,235 kg
Security	**Alarm input channels**	1
	Alarm output channels	1
	Video motion detection	Yes
Storage	**Card reader integrated**	Yes
	Compatible memory cards	MicroSD (TransFlash), MicroSDHC, MicroSDXC
Technical details	**Number of video streams**	4
	Voltage	12 V
	Warranty period	5 År
Vendor information	**Brand Name**	Ernitec
	Warranty	5 År
Video	**Portrait mode**	Yes
	Supported video modes	1080p, 720p
	Total megapixels	2 MP
	Video formats supported	H.264, H.265, M-JPEG