MPN: 0070-08117-V2

Pluto Pro 5MP kupolkamera med 2,7–13,5 mm motoriserad lins och IR 40 m, PoE, IP66, IK10 - NDAA

Pluto-PX-325IR



Ernitec vandalresistent IP-kupolkamera som kombinerar avancerad teknik och robust konstruktion och är ett idealiskt val för omfattande övervakningslösningar.

- 1/2,8” progressiv skannande CMOS
- 2592×1944 @ 25/30fps (5MP)
- 2,7–13,5 mm motoriserad lins
- Smart IR upp till 40 m
- WDR, 3D DNR, ROI, HLC, BLC, avdimning
- Stöd för ansikts-, person- och fordonsdetektion och bildfångst
- 1/1 ljud in/ut, 1/1 larm in/ut
- Strömförsörjning DC12V / PoE (IEEE 802.3af)
- IP66, IK10
- 5 års garanti

Specifikationer

Audio	**Audio input channels**	1 kanaler
	Audio output channels	1 kanaler
Camera	**Camera pan control**	No
	Lens viewing angle, horizontal	87.5-26 °
	Lens viewing angle, vertical	64.8-19.9 °
	Minimum illumination	0,03 lx
	White balance	Auto
Design	**Housing material**	Metal
	IK code	IK10
	International Protection (IP) code	IP66
	Mounting type	Ceiling/Wall/Pole
	Product colour	White
	Weatherproof	Yes
Image sensor	**Sensor type**	1/2.8” Progressive Scan CMOS
Legal Information	**ADR Information**	No restrictions
	Country of Origin	Vietnam
	Tariff No.	8525890000
	UNSPSC Code	46171610
Lens system	**Focal length range**	2.7 - 13.5 mm

Management features	**Firmware upgradeable**	Yes
	Remotely operated	Yes
	Web browser	Yes
	Web-based management	Yes
Network	**Ethernet LAN**	Yes
	Wi-Fi	No
Night vision	**Infra-red wavelength**	850 nm
	LED type	IR
	Night vision	Yes
	Night vision distance	40 m
Operational conditions	**Operating relative humidity (H-H)**	0-95 %
	Operating temperature (T-T)	-40-60 ° C
Other features	**Dimensions (WxDxH)**	140x140x109 mm
Package dimensions	**Gross Weight (Package, kg)**	1 kg
Performance	**Alarm input/output**	Yes
	Connectivity technology	Wired
	Day/night mode	Yes
	NDAA Compliance	Yes
	Placement supported	Indoor & outdoor
	Type	IP security camera
	Wide Dynamic Range (WDR)	Yes
Ports & interfaces	**Ethernet LAN (RJ-45) ports**	1
Power	**Power consumption (max)**	7,5 W
	Power over Ethernet (PoE)	Yes
	Power source type	PoE
Product dimensions	**Net Weight (Product, kg)**	0,73 kg
Security	**Alarm input channels**	1
	Alarm output channels	1
Storage	**Card reader integrated**	Yes
	Maximum memory card size	256 GB
Technical details	**Warranty period**	5 År
Vendor information	**Brand Name**	Ernitec
	Warranty	5 År
Video	**Back Light Compensation (BLC)**	Yes
	Maximum resolution	2592x1944 pixlar
	Total megapixels	5 MP
	Video compression formats	H.264, H.265, M-JPEG
	Video intelligence analytic	Yes