

- 4K HD solution
- · Using all-imported industrial-grade LED screen
- · Designed for CCTV
- · High brightness, high contrast, high definition
- Adapts to the latest 3D digital filtering and 3D digital noise reduction technology
- · Picture fast response
- · 178° wide viewing angle
- $\cdot\quad$ Ensures that the image display is not deformed
- \cdot 24/7 working status, working continuously for 5 years
- Metal chassis design, anti-static, anti-magnetic field, anti-interference, no radiation
- · Menu with convenient controller



















DIMENSIONS (MM)







INDUSTRIAL MONITOR 28" 4K

Version no.: 1.0 (Jan 2023) Page 1 of 2



DISPLAY CHARACTERISTICS		
Mode name	0070-24128	
Screen size	28"	
Active display area (mm)	620.93mm(W)×341.3mm(H)	
Display mode	16:9	
Led type	TFT-LED	
Resolution	3840 × 2160	
Display colour	1.073G	
Pixel pitch (mm)	0.1617(H)×0.1617(V)	
Brightness (nits)	350cd/m ²	
Contrast ratio	1000:1	
Viewing angle	178(H)/178(V)	
Response time	5ms	
Backlight	LED	

INPUT & OUTPUT		
HDMI 2.0	3	
DP	1	
USB	1	
Power	1	
Speaker	2x 3W(Stereo)	

VIDEO		
Colour system	PAL/NTSC/SECAM	
OSD control	Auto adjust, Brightness, Contrast, Hori. / Vert. Position, Clock, Phase, Color, Language	
3D comb filter	YES	
Support Picture in Picture (PIP)	YES	

POWER & MOUNT		
Power	AC100V~240V,50/60Hz	
Working temperature	30 to +85 °C	
Power consumption	<40W	
Menu	English, German, French	
Mounting/weight	VESA mount/7kg	
MTBF	50000Hours	
Accessories	Industrial PSU, screw, cable holder, quick start guide	
Warranty	5 years	



INDUSTRIAL MONITOR 28" 4K

Version no.: 1.0 (Jan 2023) Page 2 of 2